

### PRODUCT No. 6681

### Pump for diesel fuel and light heating oils 36 l/11301



(Illustrative photograph)

#### Technical data

Power	230 V
Transmission capacity	approx. 36 l/min
Suction hose	1,6 m
Viscosity	5 – 20 mPas
Temperature of the medium	-10 / +35°C
Thread (connecting/barrel)	G 1" / G 2"
Protection	IP 44
Electrical cable	2 m
Max. suction height	2 m
Weight	3,6 kg
Width (pump)	132 mm
Depth (pump)	137 mm
Height (pump)	205 mm

#### Attributes

- Suction hose allows pumping from poorly accessible places.
- A manual pump is integrated in the pump.
- The pump is supplied with a suction hose with a filter – 1,6 m.
- Equipment: dispensing hose – 4m, dispensing nozzle with swivel joint, 2" fitting for barrel installation.
- Power supply – 230 V, 50 Hz, 250 W.

#### Product purpose

- Designed for pumping diesel fuel, light heating oil or undiluted antifreeze in industry, construction, agriculture, etc.

#### Additions

- Accessories can be ordered – Digital flowmeter No. 6682.
- The pump cannot be used in the food industry.
- The must not be used for combustible and explosive liquids of hazard classes AI, AII and B. AllI hazard class liquids shall not be used when the liquids are heated to a temperature above their flash point. The pump must not be used in a potentially explosive zone.