

PRODUCT No. 4791

Safety cabinet (30 gal – 114 l)



(Illustrative photograph)

Technical data

Material (thickness)	Steel (1 mm) – Double casing construction with 38 mm gap
Capacity	114 l
Shelf load capacity	159 kg
Weight	102 kg
No. of doors	2 pcs
No. of shelves	1 pcs
Width (inner/outer)	1003/1092 mm
Depth (inner/outer)	370/457 mm
Height (inner/outer)	1006/1118 mm
Certification	FM 6050 (NFPA, OSHA)

Attributes

- Made of high quality and high resistant steel – casing thickness is 1 mm.
- Equipped with a so-called piano hinge, which ensures a firm suspension of the door – it reduces air access in case of fire.
- Three-point stainless steel locking system greatly increases the level of security.
- Equipped with reflective labels alerting the storage of dangerous substances in three languages.
- Equipped with adjustable shelves by 76 mm and made of galvanized steel with a load capacity of 159 kg.
- The shelf allows liquids to be drained into an insoluble trap at the bottom of the cabinet.
- Patented system – U.LOC TM – recessed lock, which can be supplemented with a padlock (not included).
- Equipped with two vent openings with anti-ignition safety lock – at the floor and at the ceiling of the cabinet.
- Equipped with an adjustable leg to compensate for any ground inequality – to increase stability and safety.
- Double casing design with an insulation gap of 38 mm. A connector for grounding the cabinet is located on the back.
- Certified according to FM (fire resistance for 10 minutes), OSHA and NFPA standards Code 30 section 6.3.3.
- Obtained with a yellow paint similar to RAL 1021.
- The warranty period is set at 10 years.

Product purpose

- Designed for protection of workers, fire reduction and improving of productivity by storing flammable substances and chemicals in secured cabinets.