

PRODUCT No. 3086

Pump – pumping set for „lyes“ – 1000 mm

(Illustrative photograph)

Technical data

Material	Polypropylene
Engine (MI4)	230 V
Output volume Q (max.)	40 - 70 l/min
Max. viscosity of pumped substance	500 mPas
Max. density of pumped substance	1,3 kg/dm ³
Max. temperature of pumped substance	50°C
Weight	5 kg
Diameter	41 mm
Length	1000 mm

Attributes

- All parts which are in contact with the pumped substance are made of: PP, PVDF, Stainless steel (1.4571), PTFE, ETFE.
- Suitable for pumping sparce lyes, sodium hydroxide, potassium hydroxide, ammonia water, formic acid, acetic acid, etc.
- **Set includes:** MI4 engine, PP 41 – L – DL – SS pump, 2x PP ¾“ hose connection, 2,0 mm PVC hose ¾“, PP dispenser with FEP seal, 2x ¾“ hose clip, barrel adapter.

Product purpose

- Designed for pumping lyes.

Additions

- In case of higher temperature, concentration of pumped substances and viscosity, it is necessary to consult the substance resistance.
- After pumping it is necessary to rinse the pump properly.
- Do not use pumps to pump flammable substances.
- Regularly check damage and tightness of the pump and the hose connection.
- The pump may only be in the vertical position.
- The pumping height of the pump varies according to the ambient conditions and properties of the substance.

