

## PRODUCT No. 3105

### Pallet truck – four-ways



(Illustration photograph)

#### Technical data

Material	Metal/Polyurethane
Weight	92 kg
Load capacity	1500 kg
Max/min. fork height	210 - 85 mm
Fork length	1150 mm
Forks width	540 mm
Fork width	160 mm
Width	540 mm
Length	1540 mm
Height	1235 mm
Wheels (controlling/under-forks)	200x50/80x70/65x60 mm



#### Attributes

- Manually controlled low-lift pallet truck stated for manipulation with EURO pallets.
- Ready to be moved in two mutually perpendicular directions.
- When lifted up to 172 mm (12 strokes) – truck can be moved in longitudinal direction only - forward and backward.
- When lifted up to 198 mm in height – side traction is on and longitudinal traction is off.
- Robust frame is laying on turnable chassis on one side and small wheels on the other side.
- Handling with the shaft up and down will start the hydraulics system.
- Rotation of wheels in 90° can be locked as required move direction – against free rotation.
- Equipped with lever for neutral position – free movement of the shaft without lifting/lowering the load.

#### Product purpose

- Designed for manipulation with all kind of pallets.

#### Additions

- Version with 3000 kg of load capacity.
- Condition of safe and reliable usage is manipulation with truck on sturdy and flat surfaces without holes and obstacles.