

PRODUCT No. 4477

Fireproof cabinet with 60 minutes resistance – single wing doors

(Illustrative photograph)

Technical data

Material	Steel
Storage capacity	130 l
Containment capacity (shelf/basin)	20 l
Weight	319 kg
Shelf max. load capacity (evenly distributed)	30 kg
No. (doors/shelves/catching basin)	1 / 3 / 1 pcs
Diameter of air inlet/outlet	100 mm
Width (inner/outer)	490 / 635 mm
Depth (inner/outer)	410 / 620 mm
Height (inner/outer)	1620 / 1950 mm



Attributes

- Construction of the cabinet is made of steel with powder paint coating.
- Suitable for industry, laboratories, paint shops, hospitals and other similar facilities.
- Designed for regulated storing of flammables and other dangerous substances.
- Provides fire resistance class of 60 minutes resistance.
- Tested in accordance with EN 14470-1, EN 1363-1.
- Doors are lockable by two-point cylindric lock.
- Safety cabinets are obtained with air inlet/outlet of 100 mm diameter.
- Shelves are designed to contain small amount of liquids (catching basins).
- When the 50 °C temperature is exceeded, doors will close by themselves.
- Delivered with three shelves and one catching basin on the bottom.

Color variations

- Standardly white (RAL 9010).

Product purpose

- Designed for regulated storing of flammables and other dangerous substances.

Additions

- Shelf can be ordered – type 4479 (490 x 410 x 30 mm).