

TECHNICAL DATA SHEET

PRODUCT No. 3903

Magnetic sewer closure – 1000 x 1000 x 0,9 mm



(Ilustrative photograph)

Technical data

Material Isotropic magnetic foil

 $\begin{array}{lll} \text{Weight} & 3 \text{ kg} \\ \text{Pressure} & 52 \text{ g/cm}^2 \\ \text{Width} & 1000 \text{ mm} \\ \text{Depth} & 1000 \text{ mm} \\ \text{Height} & 0,9 \text{ mm} \end{array}$

Attributes

- Made of isotropic magnetic foil with permanent magnetic properities.
- Material Strontium Ferrite 90%, Chlorinated polyethylene 10%.
- Foil thickness is 0,9 mm.
- Pressure force is 52 g/cm².
- Can be use dat temperature range -20°C to +80°C its flexibility reduces at low temperatures.
- Designed for fast solving of emergency situations associated with leakage of dangerous liquids, even and clean surfaces.
- Not designed for permanent emergency locking.
- Suitable for: new types of sewer inlets of ferromagnetic material.

Color variations

- Black color.

Product purpouse

- Designed for fast solving of emergency situations associated with leakage of dangerous liquids, even and clean surfaces.

Additions

- Foils does not working with plastic materials.

Tel.: 416 823 181 MEVA-TEC s.r.o.
E-mail: info.mevatec@meva.eu Chelčického 1228
413 01 Roudnice nad Labem - Bezděkov