

PRODUCT No. 6683

Pump for diesel fuel and light heating oils 50 l/min W 50



(Illustrative photograph)

Technical data

Power	230 V
Transmission capacity	approx. 55 l/min
Suction hose	1600 mm
Viscosity	5 – 20 mPas
Temperature of the medium	-10 / +35°C
Thread (connecting/barrel)	G 1" / G 2"
Protection	IP 54
Delivery hose	4 m
Electrical cable	2 m
Max. suction height	2 m
Weight	7,3 kg
Width (pump)	245 mm
Depth (pump)	170 mm
Height (pump)	200 mm

Attributes

- Suction hose allows pumping from poorly accessible places.
- The pump is supplied with a suction hose with a filter – 1,6 m.
- Equipment: dispensing hose – 4m, dispensing nozzle with swivel joint, 2" fitting for barrel installation.
- Power supply – 230 V, 50 Hz, 330 W.

Product purpose

- Designed for pumping diesel fuel, light heating oil or undiluted antifreeze in industry, construction, agriculture, etc.

Additions

- Accessories can be ordered – Digital flowmeter No. 6684.
- The pump cannot be used in the food industry.
- The must not be used for combustible and explosive liquids of hazard classes AI, AII and B. AIII hazard class liquids shall not be used when the liquids are heated to a temperature above their flash point. The pump must not be used in a potentially explosive zone.