

PRODUCT No. 7030

Loose sorbent II. – Spilkleen plus SK 2



(Illustrative photograph)

Technical data

Material (package)	Polyethylene (PE)
Sorption ability (oil/water)	9 l / 11 l
Density	300 kg/m ³
Composition	Cellulose (60%) + kaolin (40%)
Package weight	10 kg
Sorption type	Universal
Width	400 mm
Depth	150 mm
Height	400 mm

Attributes

- Package consists of a polyethylene bag.
- For the production of Spilkleen Plus SK 2 sorbents are used pure natural resources and recycled/waste cellulose.
- High sorption capability for both oil and water.
- More suitable for indoor use.
- This is a completely non-flammable type of sorbent.
- **Recommended use:** Loose sorbent based on cellulose for sorption of hazardous liquids. Quickly and thoroughly absorbs liquids from all surfaces. Sorbent with reduced dust, non-abrasive.

Spilkleen:

- Loose sorbents for extraction of liquids.
- These are products resulting from the subsequent treatment of cellulose and the used sorbent can be easily burned.
- Higher efficiency compared to conventional granules.
- In case of interference, it is not blown by wind, the treated area is not slipped and the surface remains dry after cleaning.

Color variations

- Sorbent – grey.

Product purpose

- Designed for sorption of hazardous liquids (oils / water).