

# PRODUCT No. 7298

## Floor scale with an indicator – up to 300 kg



(Ilustrative photograph)

Technical data

Scale:

Material construction/design/weighting surface Weight Max. weighting (accuracy) Operationg temperature Width Depth Height Certification Indicator: Material Power supply Communication interface Operating temperature Desplay Dimensions FE/steel/sheet metal 90 kg 300 kg (100 g) -10°C/+40°C 1000 mm 1000 mm 90 mm For non-commercial weighting (scale cannot be verfied up to 300 kg) Plastic AC 230V RS-232 0°C/+40°C

## <u>Attributes</u>

- The scale is made of varnished steel, 4 mm thick sheet metal and the indicator is made of plastic material.
- Suitable for dry conditions with operating temperatures from -10°C to a +40°C.
- The indicator can be used both from the mains and the bulit-in battery.
- Weighting program: piece counting, addition counting, weighting of animals, automatic addition and data sending.

LED, 20 mm

248 x 156 x 160 mm

- Weighting limit with upper and lower limit settings for weight tolerance.
- Indicator: a large LCD display (52 mm), readable from large distances and at an angle of 170°, fast setting, supplied with a plastic holder on a 38 mm diameter tube, tiltable, stable on table.

### Product purpouse

- Designed for weighting, for example when receiving or dispatching goods in a dry enclosed environment.

### Additions

- The balance comes with an indicator.