

### PRODUCT No. 8151

### Mobile filling station for diesel and AdBlue® – COMBI 850/100 I - 24/12 V

(Illustrative photograph)

#### Technical data

Material	Polyethylene (PE)
Weight	121 kg
Capacity	850/100 l
Voltage	24/12 V
Output	70/25 l/min
Width	1270 mm
Depth	1070 mm
Height	1120 mm



#### Attributes

- Single-walled polyethylene container.
- Integrated partition.
- Integral dispensing nozzle holder.
- Integral filling throat.
- Integrated vent with pressure relief.
- Integral forklift pockets.
- Integrated handles, equipped with crane loops and hinged lid.
- Integral recesses for ratchet straps during transport.
- The COMBI filling station is equipped with a diesel tank (850 l) and an AdBlue tank (100 l).
- Equipped with a 24/12 V electric pump for the diesel section.
- Equipped with a submersible pump SP30 12 V with a capacity of 25 l/min for the section with AdBlue® additive.
- Equipped with 4 meters long delivery hose DN25 with automatic nozzle (without reel, indicator and filter).
- Equipped with electrical cable.
- Approved for transport according to ADR 6.5.4.4.1 b) and ADR 6.5.4.4.2 b).



#### Color variations

- Standardly in grey color.

#### Product purpose

- Designed for diesel fuel and AdBlue® additive delivery.

#### Additions

- Delivered completely assembled including lid.
- For immediate use.
- According to ADR regulations, each tank must be regularly inspected after 2,5 years.